



- Instruction:**
1. Type: Film to Film
 2. Operating Voltage: 5*7 V
 3. Response Time: $\le 10ms$
 4. Storage Temperature: $-20\text{ }^{\circ}\text{C} \sim 70\text{ }^{\circ}\text{C}$
 5. Operation Temperature/Humidity: $-10\text{ }^{\circ}\text{C} \sim 40\text{ }^{\circ}\text{C} / 20\% \sim 90\%$
 6. Hitting Life: $>10,000,000$ Times, $250\mu\text{f}$ Force;
 7. Writting Life: $>1,000,000$ Times, $250\mu\text{f}$ Force;
 8. Dielectric Material: PPO+PIH
9. Film Thickness: 0.188mm
 10. Film Thickness: 0.188mm
 11. Light transmission: $\ge 70\%$
 12. Force: $100\mu\text{g}$ or Less
 13. Absorcity: $\le 1.5\%$
 14. Insulation: $\ge 20\text{M } \Omega$
 15. Surface Hardness: $\ge 8\text{H (pena11)}$
 16. 未标注公差均 $\pm 0.3\text{mm}$

MODEL NO.	T8240A4K03	UNIT:	MM
DRAWN:		TOLERANCE:	± 0.3
DATE:	16/11/23	SCALE:	1:1
VERSION:	1.0	REV:	